

- Solution for chloramine reduction
- Exceptional Chlorine Taste and Odor Reduction based on NSF/ANSI Standard 42\*
- Reduction of other chemicals in addition to common particulates\*
- Low pressure drop
- Activated coconut carbon for purer filtration



\*Based on Internal Manufacturer's testing



Filter Cartridge has been Tested and Certified by NSF International Against NSF/ANSI Standard 42 for material requirements only.



| Part Number | Nominal<br>Dimensions | Chloramine<br>Capacity* | Initial Pressure Drop*<br>(PSI) |
|-------------|-----------------------|-------------------------|---------------------------------|
| CB2510CM01  | 2.5" x 10"            | 1,000gals@1GPM          | <5psi@1GPM                      |
| CB2520CM01  | 2.5" x 20"            | 2,000gals@2GPM          | <6psi@2GPM                      |
| CB4510CM01  | 4.5" x 10"            | 2,500gals@3GPM          | <5psi@3GPM                      |
| CB4520CM01  | 4.5" x 20"            | 5,000gals@6GPM          | <6psi@6GPM                      |



## **Important Notice**

Performance claims are based on a complete system. The filter must be used in an approved system and operating according to the system's specifications. Each application must be followed in order for the filter to perform properly.

## **Warnings**

American Carbon Block filters are to only be used with microbiologically safe water. The filter is not designed to kill or remove bacteria or viruses. All information is based on data believed to be reliable. This information is offered for verification and evaluation only and is not intended to be a warranty.

